OSRAM

LEDriving SL PY21W

Ideal replacement for any vehicle



Suitable for various vehicle exterior applications

Available in Amber



Replaces conventional PY21W lamps

Easy upgrade to LED technology with plug & play solutions



Reliable OSRAM quality stands for less lamp replacements

4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for PY21W

LEDriving SL PY21W replacement lamps offer a modern and intense light. These replacement lamps are suitable for all conventional PY21W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product datasheet

Technical data

Product information

Product type (off-road vs. on-road)	Off-road ≙ PY21W	
Application (Category and Product specific)	Mainly used for signal/ indicator applications	

General Product Information

Global order reference	7507DYP

Electrical Data

Power input	1.5 W
Nominal voltage	12.0 V
Nominal wattage	1 W
Test voltage	13.5 V
Power input tolerance	±10 %

Photometric Data

Nominal luminous flux	50 lm
Luminous flux tolerance	±25 %
Light color LED	Yellow

Physical Attributes & Dimensions

Diameter	25.0 mm
Product weight	16.00 g
Length	52.5 mm
Lamp base	BAU15s

Lifetime Data

Lifespan B3	1500 hr
Lifespan Tc	4000 hr
Guarantee	4 years

Capabilities

Technology	LED ¹⁾

 $^{^{1)}\, {\}rm Light\text{-}emitting}\,\, {\rm diode}\, {\rm lamp}$

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)		
Date of declaration	09-07-2024	

Product datasheet

Primary article identifier	4062172401517 4062172152242		
Candidate list substance 1	Lead		
CAS No. of substance 1	7439-92-1		
Safe use instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.		
Declaration no. in SCIP database	bcf00c1f-4751-4bd7-8ce1-efa17d78d8a9		

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172152259	LEDriving SL ≙ PY21W		- x - x -	1.96 dm ³	

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

File



Brochures

LEDriving Retrofits - Exchange overview (EN)

Safety advice

Canbus compatibleColoured lamps for usage behind coloured glass

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

