

# LEDDriving SL P13W

Ideal replacement for any vehicle



**Suitable for various vehicle exterior applications**

Available in Cool White



**Replaces conventional P13W lamps**

Easy upgrade to LED technology with plug & play solutions



**Reliable OSRAM quality stands for less lamp replacements**

4-year OSRAM guarantee (refer to [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee) for precise conditions)



### Suitable LED replacement for P13W

LEDDriving SL P13W replacement lamps offer a modern and intense light with a color temperature up to 6,000 Kelvin. These replacement lamps are suitable for all conventional P13W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

# Product datasheet

## Technical data

### Product information

Product type (off-road vs. on-road)	Off-road $\triangleq$ P13W
Application (Category and Product specific)	Mainly used for daytime running light applications

### General Product Information

Global order reference	828DWP
------------------------	--------

### Electrical Data

Power input	1.90 W
Nominal voltage	12.0 V
Nominal wattage	1 W
Test voltage	13.5 V
Power input tolerance	$\pm 10$ %

### Photometric Data

Nominal luminous flux	130 lm
Luminous flux tolerance	$\pm 15$ %
Color temperature	6000 K
Light color LED	Cool white

### Physical Attributes & Dimensions

Diameter	23.0 mm
Product weight	10.50 g
Length	48.3 mm
Lamp base	PG18.5d-1

### Lifetime Data

Lifespan B3	1500 hr
Lifespan Tc	4000 hr
Guarantee	4 years

### Capabilities

Technology	LED <sup>1)</sup>
------------	-------------------

<sup>1)</sup> Light-emitting diode lamp

### Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)

## Product datasheet


Date of declaration	06-09-2024
Primary article identifier	4062172401432   4062172150279
Candidate list substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe use instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration no. in SCIP database	86a80c4c-80ba-4d88-b8fd-60cafbfef775

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172150279	LEDriving SL $\triangleq$ P13W	Folding carton box 1	34 mm x 34 mm x 58 mm	0.07 dm <sup>3</sup>	14.00 g
4062172150286	LEDriving SL $\triangleq$ P13W	Shipping carton box 10	178 mm x 76 mm x 67 mm	0.91 dm <sup>3</sup>	166.00 g
4062172401432	LEDriving SL $\triangleq$ P13W	Blister 1	95 mm x 27 mm x 135 mm	0.35 dm <sup>3</sup>	20.00 g
4062172401449	LEDriving SL $\triangleq$ P13W	Shipping carton box 10	156 mm x 144 mm x 110 mm	2.47 dm <sup>3</sup>	257.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Download Data

File
 Brochures LEDriving Retrofits - Exchange overview (EN)

#### Safety advice

Canbus compatible Coloured lamps for usage behind coloured glass

#### Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

#### Application advice

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

