Product family datasheet

TYREinflate 450



Rapid Inflation Time
Inflate the tire to the desired pressure in ca. 3.5 minutes**



Wind-up Cable
Winding/unwinding mechanism for a neatly rolled up cable



LED Light
Easy to operate even in darkness and in low light conditions



Rapid tyre inflator with wind-up cable

The OSRAM Tyreinflate 450 can inflate a tyre from flat in 3.5 minutes**. Comes with auto stop feature to accurately get the desired pressure for your tyre. Includes a backlit digital display and white LED light for optimal illumination in darkness.The Tyreinflate 450's flat, solid design makes the unit stable whilst in use, as well as the wind up cable eliminating any messy wires and helping you get back on the road faster. Comes complete with three piece adaptor kit for bicycle tyres, balls and other inflatables.**based on inflating a 13" tyre from flat to 2.41 BAR

© 2024, OSRAM GmbH. All rights reserved.

Product family datasheet

Technical data

	Electrical data	Dimensions & weight			Additional product data	Capabilities
Product description	**Nominal voltage**	**Height**	**Width**	**Length**	**Display Type**	**Fuse**
TYRE inflate 450	11.1 V	180.0 mm	88.0 mm	197.0 mm	Digital	10 A

	Country specific categorizations	Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)		
Product description	**Order reference**	**Date of Declaration**	**Primary Article Identifier**	**Candidate List Substance 1**
TYRE inflate 450	OTI450	07-03-2024	4052899620216	Lead

Product description	**CAS No. of substance 1**	**Safe Use Instruction**	**Declaration No. in SCIP database**
TYRE inflate 450	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	dda41c6e-d521-4522-a227-e170d9cf4d66

© 2024, OSRAM GmbH. All rights reserved.

Product family datasheet

Download Data

	File
	User instruction TYREinflate 450
	Product movie TyreInflate How to Video (EN)
	Product movie TyreInflate 450 Product Video (EN)
	Video OSRAM TYREinflate 450: Rapid tyre inflator with wind-up cable, LED light and digital display
	Video OSRAM TYREinflate How To: Change your vehicle's tyre pressure easily

Safety advice
Product won't exceed noise levels of more than 90 dB

Legal advice
CE and EAC compliant

* for precise conditions please refer to: www.osram.com/am-guarantee

** based on inflating a 13” tyre from flat to 2.41 BAR

Application advice:

For more detailed application information and graphics please see product datasheet.

Disclaimer:

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

Application advice
For more detailed application information and graphics please see product datasheet.

Disclaimer
Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2024, OSRAM GmbH. All rights reserved.