Product datasheet

TYREinflate 1000



Rapid Inflation Time
Inflate the tire to the desired pressure in ca. 2 minutes**



Wind-up Cable
Winding/unwinding mechanism for a neatly rolled up cable



LED Light
Easy to operate even in darkness and in low light conditions



Rapid tyre inflator with wind-up cable

The OSRAM Tyreinflate 1000 is a rapid digital tyre inflator with a backlit digital display for easy, accurate pressure readings. Includes an auto stop feature to get the exact desired pressure needed to accurately inflate your tyres. The auto set on the Tyreinflate 1000 is incredibly easy to set up - just turn the dial to the pressure you require, click to set, then press start. The inflator will automatically stop once the correct pressure has been reached.A wind-up power cable eliminates messy wires and a 2 minute inflation time* gets you on the road and where you need to be quickly. The power cable is long enough (3.5 m) to reach all tyres around your vehicle. The large on/off button and the LED directional light make the Tyreinflate 1000 easy to use in darkness and emergencies – keeping you prepared for whatever may happen on the road.Includes 3-piece adaptor for bicycles, balls and other inflatables.**based on inflating a 13” tyre from flat to 2.41 BAR

© 2024, OSRAM GmbH. All rights reserved.

Product datasheet

Technical data


Product information

Order reference	OTI1000
Inflation time	2 min
Max Pressure	5.5 bar
Air Hose Length	70 cm
Power Cord Length	3.5 m
Charge Time (h)	N/A
Display Size	76 x 48 mm
Measuring Units	PSI, kPa, bar
Accuracy (bar)	±0.1 bar
Flow rate (l/min)	tbc

Electrical data

Nominal wattage	180.00 W
Nominal voltage	11.1 V
Operating Voltage	12 V
Power Source	12 V Fused Plug

Dimensions & weight



Length	200.0 mm
Width	88.0 mm
Height	219.0 mm

Additional product data

Display Type	Digital
Noise Level (dB)	90 dB
Recommended to Use With	Car, Small Van, 4X4, Large Van, Trailer

© 2024, OSRAM GmbH. All rights reserved.

Capabilities

Accessories	Adaptors for: Balls, Air Mattress, Bikes
Fuse	15 A

Country specific categorizations

Order reference	OTI1000

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)	
Date of Declaration	07-03-2024
Primary Article Identifier	4052899620223
Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	b0abf529-311b-4f43-8c8e-139c08188c8b



Detail



Detail



Detail

© 2024, OSRAM GmbH. All rights reserved.

Product datasheet



Detail



Detail



Detail



Detail



Product Info Graphics



Product Info Graphics

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899620223	TYRE inflate 1000	Folding carton box 1	232 mm x 95 mm x 216 mm	4.76 dm^3	1626.00 g
4062172166539	TYRE inflate 1000	Shipping carton box 4	401 mm x 251 mm x 248 mm	24.96 dm^3	6893.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

File

© 2024, OSRAM GmbH. All rights reserved.

	User instruction TYREinflate 1000
	User instruction TYREinflate 1000
	Movie application OSRAM TYREinflate 1000 Application Video Short (EN)
	Product movie TyreInflate How to Video (EN)
	Product movie TyreInflate 1000 Product Video (EN)
	Video OSRAM TYREinflate 1000: Rapid tyre inflator with wind-up cable, large digital display and LED light
	Video OSRAM TYREinflate How To: Change your vehicle's tyre pressure easily

Safety advice
Product won't exceed noise levels of more than 90 dB

Legal advice
CE and EAC compliant

* for precise conditions please refer to: www.osram.com/am-guarantee

** based on inflating a 13” tyre from flat to 2.41 BAR

Application advice:

For more detailed application information and graphics please see product datasheet.

Disclaimer:

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

Application advice
For more detailed application information and graphics please see product datasheet.

Disclaimer
Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2024, OSRAM GmbH. All rights reserved.