

# BATTERYcharge 908



**Start/Stop compatible**

Suitable for vehicles with Start/Stop system



**Winter mode**

Protects batteries in cold temperatures



**9-stage charging cycle**

For easy charging of Lead Acid/AGM batteries



**Smart battery charger and maintainer with multi-stage charging cycle**

The OSRAM BatteryCharger 908 is a 8A smart charger and battery maintainer for 12V and 24V vehicles including most cars, vans and small trucks. Maintains and charges a vehicle's battery through a 7 stage charging cycle at the touch of a button for Lithium batteries, with only a 9-stage cycle of Lead Acid/AGM batteries. Includes a backlit LCD digital display to keep things easy even in low light. A host of safety features including reverse polarity and short-circuit protection, keeps both the user and the vehicle safe. Be sure that the charger is maintaining your car battery as it automatically changes to long-term maintenance mode when the vehicle's battery is full.

# Product datasheet

## Technical data

### Product information

Application (Category and Product specific)	Smart battery charger
---	-----------------------


### Electrical Data

Charge Rate (Up to)	8.0 A
Maintenance Charge (up to)	4.0 A
Max battery capacity	150 Ah
Min battery capacity	70 Ah

### Physical Attributes & Dimensions

Length	185.0 mm
Width	106.0 mm
Height	70.0 mm

### Dimensions & weight



Power Cable Length	1.5 m
Clamps Cable Length	1.5 m

### Additional product data

Recommended to Use With	Motorcycle, Car, SUV, Van, Small Truck
Stages: Lead, AGM, EFB	9
Stages: Lithium	7
Battery Connection	O-rings, Crocodile Clamps

### Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)

## Product datasheet






<b>Date of declaration</b>	26-06-2024
<b>Candidate list substance 1</b>	Lead
<b>CAS No. of substance 1</b>	7439-92-1
<b>Safe use instruction</b>	The identification of the Candidate List substance is sufficient to allow safe use of the article.
<b>Declaration no. in SCIP database</b>	39a90b38-e51d-44ff-8a96-fe9eea625c68

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899620629	BATTERY charge 908		- x - x -	29.37 dm <sup>3</sup>	

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Download Data

File
 User instruction BATTERYcharge
 Movie application BatteryCharge How to Video (ITA)
 Movie application BatteryCharge How to Video (EN)
 Product movie OSRAM BATTERYcharge OEBCS908 Product Video (EN)
 Product movie OSRAM BATTERYcharge OEBCS908 Product Video (DE)

#### Legal advice

\*for precise conditions please refer to:

[www.osram.com/am-guaranteeApplication](http://www.osram.com/am-guaranteeApplication) advice:

For more detailed application information and graphics please see product datasheet.

#### Application advice

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

