

HBO R & HXP R ≤ 200W with Reflector



Användningsområde

- Laboratory & Analysis
- UV Curing
- Fiber Illumination
- Microscopy
- Solar Simulation

Produkttegenskaper

- High luminance / radiance with intense point source
- Broad spectral distribution in the visible and ultraviolet range
- Enhanced UV characteristics available on some types
- High arc stability





HBO R 103W

Datablad produktfamilj

Tekniska data

Produktbeskrivning	Elektriska data			Livslängder
	Nominell watttal	Brinns্পänning	Lampspänning	Average Rated Life
HBO R 103 W/45	103 W	20...25 V ²⁾	4.0...5.0 A	300 hr
HXP R 120 W/45 C VIS ¹⁾	120 W	60...90 V ³⁾	1.4 A	2000 hr
HXP R 120 W/45 C UV ¹⁾	120 W	60...90 V ³⁾	1.4 A	2000 hr
HXP R 200 W/45 M ¹⁾	200 W	60...96 V ³⁾	3.4 A	2000 hr

¹⁾ To be operated with OSRAM PT VIP EVG

²⁾ Initiala elektriska värden

³⁾ Initialt spänningsområde

Datablad produktfamilj

Säkerhetsanvisningar

Due to their high luminance, UV radiation, and high internal pressure in the hot state, HBO and HXP lamps may only be operated in enclosed lamp casings designed for their operation. Since mercury is released if the lamp breaks, special safety precautions must be taken. More information is available upon request, or can be found in the leaflet or operating instructions included with the lamp. You can also review our Product Safety Guide.

Applikationsråd

För mer detaljerad applikationsinformation och grafik, vänligen se produktdatablad

Friskrivningsklausul

Kan ändras utan föregående notifiering. Felaktigheter och försummelse undantagna. Se alltid till att använda den senaste utgåvan.