


## FX-DCS -G1-CM2PJ-IP67-TOPKIT5

LINEARlight Flex DIFFUSE IP67 connector | Accessories for Flexible LED strips



### Product family features

- Quick and easy installation
- Compatible with Linearlight Flex
- Compatible with TEC Flex


### Product family benefits

- Simple installation, no tools or soldering required (CONNECTsystem)
- Reduced installation time (CONNECTsystem)
- Can be connected to the front of the module or at division points (CONNECTsystem)
- Low profile (CONNECTsystem)

## Product datasheet

### Technical data

#### Dimensions & weight



Product weight	102.30 g
Length	260.0 mm
Width	150.0 mm
Height	30.0 mm



#### Logistical data

Commodity code	853669909900
----------------	--------------

#### Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	12-02-2022
Primary Article Identifier	4052899452053
Declaration No. in SCIP database	In work

### Download Data

File	
	User instruction LINEARLIGHT Flex Diffuse Installation Guide - Naed Version (EN)
	Brochures Light is freedom of design (EN)

## Product datasheet

---

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899452053	FX-DCS -G1-CM2PJ-IP67-TOPKIT5	Shipping carton box 10	195 mm x 295 mm x 160 mm	9.20 dm <sup>3</sup>	1268.00 g

---

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.