

FX-QMS-G1 -CFDB-300

Surface slim profile 15x6mm | Accessories for Flexible LED strips

Product family features

- Can be easily combined with covers for homogeneous light distribution
- Clips for easy installation and maintenance
- Compatible with LINEARlight Flex and TEC Flex
- Ideal even for lighting in confined spaces
- Compatible with LF Protect and TF Protect without cover

Product family benefits

- Plenty of freedom for attractive design and perfect functioning
- Quick and easy installation
- Aluminum profile robust and corrosion-resistant thanks to anodization
- Minimum installation dimensions thanks to compact design

Page 1 of 4

Product datasheet

Technical data

Dimensions & weight



| Length | 3000 mm |
|----------------|---------|
| Product weight | 51.75 g |
| Width | 11.0 mm |
| Height | 4.0 mm |

Additional product data

| Predecessor EAN | 4052899447059 |
|-----------------|---------------|
| | |

Logistical data

Environmental information

| Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh) | | | |
|---|------------------------------------|--|--|
| Date of Declaration | 30-08-2022 | | |
| Primary Article Identifier | 4052899446991 | | |
| Candidate List Substance 1 | No declarable substances contained | | |
| Declaration No. in SCIP database | No declarable substances contained | | |

Download Data

| | File |
|----------|---|
| 太 | Product Datasheet Specification Sheet Slim Track FX-QMS-G1-T45D19H19-300 (EN) |
| <u> </u> | Product Datasheet Specification Sheet Slim Track FX-QMS-G1-TU15H6-300 (EN) |

Product datasheet

| 7 | Product Datasheet Specification Sheet Slim Track FX-QMS-G1-TU15H6W3-300 (EN) |
|----------|---|
| 7 | Product Datasheet Specification Sheet Slim Track FX-QMS-G1-TU16H12LS-300 (EN) |
| 大 | Product Datasheet Specification Sheet Slim Track FX-QMS-G1-TU16H12W3-300 (EN) |
| 7 | Product Datasheet Specification Sheet_Slim Track FX-QMS-G1-TU16H12-300 (EN) |
| 7 | Product Datasheet Specification Sheet Wide Profile FX-QMS-G1-TR19H16-300 |
| 乙 | Brochures Light is freedom of design (EN) |

Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer. In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer. Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistical Data

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|---------------------|------------------------------|--------------------------------------|---------------|--------------|
| 4052899446991 | FX-QMS-G1 -CFDB-300 | Shipping carton box 40 | 3060 mm x 225 mm x 225 mm | 154.91 dm³ | 3293.00 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Product datasheet

| \Box | | 1 ~ 1 | im | or |
|--------|-----|-------|----|------|
| v | ISC | LdI | ш | IEI. |
| _ | | | | ш. |

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.