

## Round surface slim profile 19x16 mm

### Accessories for Flexible LED strips



#### Product family features

- Can be easily combined with covers for homogeneous light distribution
- Clips for easy installation and maintenance
- Compatible with Linearlight Flex
- Ideal even for lighting in confined spaces
- Compatible with TEC Flex

#### Product family benefits

- Plenty of freedom for attractive design and perfect functioning
- Quick and easy installation
- Aluminum profile robust and corrosion-resistant thanks to anodization
- Minimum installation dimensions thanks to compact design


Product family datasheet

Technical data


	Dimensions & weight		Logistical data	Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)
Product description	Length	Product weight	Commodity code	Date of Declaration
FX-QMS-G1 -EFGP-TR19H16	160 mm	100 g	39269097900	11-02-2022
FX-QMS-G1 -EFGH-TR19H16	160 mm	100 g	39269097900	02-02-2022
FX-QMS-G1 -TR19H16-PENDANTKIT	150 mm	19200 g	73269098900	11-02-2022
FX-QMS-G1 -CFDB-300	3000 mm	5175 g	39169050900	30-08-2022
FX-QMS-G1 -CFTL-300	3000 mm	5850 g	39269097900	11-02-2022

Product description	Primary Article Identifier	Candidate List Substance 1	Declaration No. in SCIP database
FX-QMS-G1 -EFGP-TR19H16	4052899999985	No declarable substances contained	No declarable substances contained
FX-QMS-G1 -EFGH-TR19H16	4052899999909	No declarable substances contained	No declarable substances contained
FX-QMS-G1 -TR19H16-PENDANTKIT	4052899600034	No declarable substances contained	No declarable substances contained
FX-QMS-G1 -CFDB-300	4052899446991	No declarable substances contained	No declarable substances contained
FX-QMS-G1 -CFTL-300	4052899999749	No declarable substances contained	No declarable substances contained


Product family datasheet



FX-QMS-G1-EFGP-TR19H16



FX-QMS-G1-EFGH-TR19H16



FX-QMS-G1-TR19H16-PENDANTKIT



729001\_FX-QMS-G1-CFDB-300



729069\_FX-QMS-G1-CFDB-300



FX-QMS-G1-CFTL-300

# Product family datasheet









## Application advice

For more detailed application information and graphics please see product datasheet.

## Sales and Technical Support

Sales and Technical Support [www.osram.com](http://www.osram.com)

## Download Data

File	
	Product Datasheet Specification Sheet Wide Profile FX-QMS-G1-TR19H16-300
	Brochures Light is freedom of design (EN)
	Product Datasheet Specification Sheet Slim Track FX-QMS-G1-T45D19H19-300 (EN)
	Product Datasheet Specification Sheet Slim Track FX-QMS-G1-TU15H6-300 (EN)
	Product Datasheet Specification Sheet Slim Track FX-QMS-G1-TU15H6W3-300 (EN)
	Product Datasheet Specification Sheet Slim Track FX-QMS-G1-TU16H12LS-300 (EN)
	Product Datasheet Specification Sheet Slim Track FX-QMS-G1-TU16H12W3-300 (EN)
	Product Datasheet Specification Sheet Slim Track FX-QMS-G1-TU16H12-300 (EN)

Product family datasheet

Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer. In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer. Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899999985	FX-QMS-G1 -EFGP-TR19H16	Shipping carton box 400	175 mm x 145 mm x 110 mm	2.79 dm <sup>3</sup>	506.00 g
4052899999909	FX-QMS-G1 -EFGH-TR19H16	Shipping carton box 400	175 mm x 145 mm x 110 mm	2.79 dm <sup>3</sup>	506.00 g
4052899600034	FX-QMS-G1 -TR19H16-PENDANTKIT	Shipping carton box 10	220 mm x 220 mm x 130 mm	6.29 dm <sup>3</sup>	2230.00 g
4052899446991	FX-QMS-G1 -CFDB-300	Shipping carton box 40	3060 mm x 225 mm x 225 mm	154.91 dm <sup>3</sup>	3293.00 g
4052899999749	FX-QMS-G1 -CFTL-300	Shipping carton box 40	3020 mm x 80 mm x 30 mm	7.25 dm <sup>3</sup>	2880.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.