

# Recessed wide profile 26x25mm

Accessories for Flexible LED strips



#### Product family features

- Can be easily combined with covers for homogeneous light distribution
- Clips for easy installation and maintenance
- Compatible with Linearlight Flex
- Ideal even for lighting in confined spaces
- Compatible with TEC Flex

## Product family benefits

- Plenty of freedom for attractive design and perfect functioning
- Quick and easy installation
- Aluminum profile robust and corrosion-resistant thanks to anodization
- Minimum installation dimensions thanks to compact design


## Product family datasheet

### Technical data

	Dimensions & weight		Logistical data	Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)	
Product description	Length	Product weight	Commodity code	Date of Declaration	
FX-QMW-G1 -CRD-300	3000 mm	28200 g	39169050900	30-08-2022	
FX-QMW-G1 -CFTP-300	3000 mm	1590 g	39269097900	02-02-2022	

Product description	Primary Article Identifier	Candidate List Substance 1	Declaration No. in SCIP database
FX-QMW-G1 -CRD-300	4052899447035	No declarable substances contained	No declarable substances contained
FX-QMW-G1 -CFTP-300	4052899999787	No declarable substances contained	No declarable substances contained

## Product family datasheet



## Download Data

	File
<b>Z</b>	Product Datasheet Specification Sheet_ Wide Track FX-QMW-G1-TK30D46H27-300 (EN)
<b></b>	Product Datasheet Specification Sheet_Wide Track FX-QMW-G1-TU26H8-300 (EN)

### Product family datasheet

'n	ä		ı.	١.
٠	т		г	П
		ĕ	٠	4
	В	4		ц

Product Datasheet

Specification Sheet Wide Track FX-QMW-G1-TU26H25W2-300 (EN)



**Product Datasheet** 

Specification Sheet Wide Track FX-QMW-G1-TU26H25-300 (EN)



Product Datasheet

Specification Sheet Wide Track FX-QMW-G1-TU26H25W10-300

#### Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer. In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer. Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

#### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899447035	FX-QMW-G1 -CRD-300	Shipping carton box 40	3020 mm x 200 mm x 200 mm	120.80 dm³	13300.00 g
4052899999787	FX-QMW-G1 -CFTP-300	Shipping carton box 40	3020 mm x 80 mm x 30 mm	7.25 dm³	1176.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.