


## PrevaLED BRICK HP Z2

LED modules for industry and outdoor applications



### Product family features

- Module efficacy: up to 186 lm/W
- Average lifetime (L80 B10): up to 100,000 h (temperature up to  $T_c = 85^\circ\text{C}$ )
- Available with color temperature: 2,200 K, 2,700 K, 3,000 K and 4000 K
- Available with CRI > 70 and CRI > 80
- Initial color consistency:  $\leq 5$  SDCM
- CE marked, ENEC certified
- Type of protection: IP20

### Product family benefits

- High-performance module for outdoor and street lighting
- Dimensions aligned with Zhaga book 15
- Compatible with third party optics, e.g. from LEDIL
- Up to 176 lm/W module efficiency for demanding lighting solutions
- NTC for on-module temperature observation

### Areas of application

- Outdoor application
- Street lighting
- Industry
- Highbay lighting
- Area lighting

## Product family datasheet

---

### Application advice

For more detailed application information and graphics please see product datasheet.

---

### Sales and Technical Support

Sales and Technical Support [www.osram.com](http://www.osram.com)

---

### Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.