

LEDinspect HEADTORCH250

Inspectionlights





Motion Sensor Activation Easily control light during hands free use



250 Lumen Two light functionsHigh: Up to 250 lmLow: Up to 140 lm



60° Flex Adjustable light angle to get the light to the desired position



2-year-OSRAM guarantee*

Systematic quality assurance measures underpin the premium workmanship and functionality of our products. Innovative technology and excellent quality really pay dividends for our customers.



Light is versatile

This high-quality headtorch from OSRAM is perfect for professional and private use. With two light functions - high up to 250lm and low up to 140lm, there is a light output to suit a wide variety of tasks. The integrated motion sensor technology allows for hassle-free, hands-free working and the option for the 60° tilt angle provides flexibility to give light where needed. The rechargeable battery allows up to 3.5h of operation at high power or up to 6h at low power. A USB Type-C charging cable and the corresponding power adaptor are included in the scope of supply. In accordance with IP54 protection rating, this headtorch has protection against ingress of particles and against splashing water and is tested for impact resistance in accordance with IK08. The LEDinspect HEADTORCH 250 has soft pads inside and additionally an adjustable strap for optimal wearing comfort and is therefore ideal as a light for craft activities, car repairs and in everyday life. In addition, OSRAM grants a 2-year guarantee*

Technical data

Product information

| Order reference | LEDIL404 |
|---|-----------------------|
| Application (Category and Product specific) | LED inspection lights |

Electrical data

| Nominal wattage | 5.55 W |
|-----------------|--------|
| Nominal voltage | 3.7 V |


Photometrical data

| Color temperature | 5700 К |
|-------------------|--------|
| Luminous flux | 250 lm |
| Light color LED | White |

LED module information

| Number of LEDs per module | 1 |
|---------------------------|---|
|---------------------------|---|

Dimensions & weight



| Product weight | 105.00 g |
|----------------|----------|
| Length | 67.0 mm |
| Width | 42.0 mm |
| Height | 45.0 mm |

Colors & materials

| Base color | Black / Orange |
|------------|----------------|
| | |

Lifespan

Guarantee

2 years

Additional product data

| Type of Battery | Rechargeable | |
|------------------------------|----------------------------------|--|
| Number of included batteries | 1 | |
| Scope of battery | Yes | |
| Battery | High-quality lithium-ion battery | |

Capabilities

| Technology | LED |
|------------|-----|
| | |

Certificates & standards

| Standards | CE/EMC/MSDS/ROHS |
|-----------|------------------|
| IK Class | IK08 |

Country specific categorizations

LEDIL404

Environmental information

| Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh) | | |
|---|--|--|
| Date of Declaration | 08-03-2024 | |
| Primary Article Identifier | 4062172354875 | |
| Candidate List Substance 1 | Lead | |
| CAS No. of substance 1 | 7439-92-1 | |
| Safe Use Instruction | The identification of the Candidate List substance is sufficient to allow safe use of the article. | |
| Declaration No. in SCIP database | bdeca20c-87d7-47fc-a8d4-ed431387b196 | |





Detail

Detail

Logistical Data

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|---------------------|---------------------------------|---|----------------------|--------------|
| 4062172354875 | INSPECTION LAMP | Folding carton box 1 | 80 mm x 66 mm x 98 mm | 0.52 dm³ | 135.00 g |
| 4062172354882 | INSPECTION LAMP | Shipping carton box 6 | 218 mm x 176 mm x 118 mm | 4.53 dm ³ | 2510.00 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

| | File |
|---|--|
| 7 | User instruction LEDinspect HEADTORCH 250 |

Application advice:

For more detailed application information and graphics please see product datasheet and user instruction.

*for precise conditions please refer to:

www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

