Product datasheet

LEDinspect SLIM MAX1000

Inspectionlights

Dimmer Switch
Individually adjustable brightness levels with up to 1000 lm

1000 Lumen
Bright, white LED light and uniform light distribution

Multi-Angle Light Output
High flexibility due to individual adjustment of the light beam

2-year-OSRAM guarantee*
Systematic quality assurance measures underpin the premium workmanship and functionality of our products. Innovative technology and excellent quality really pay dividends for our customers.

Light is versatile

This high-quality inspection light is perfect for professional and private use. With an integrated dimmer, you can select the appropriate brightness level with up to 1000lm for the task at hand with the SLIM MAX 1000. The ultra slim design combined with multi-angle positioning gives maximum flexibility and adjustability to give light exactly where needed. The SLIM MAX 1000 is rechargeable and cordless with Li-ion battery and can therefore provide constant light output. The lamp has an operating time of up to 1.5h with high light output or up to 10,5h with low light output. A USB Type-C charging cable is included in the scope of supply. In accordance with the IP protection class IP65, this inspection

© 2026, OSRAM GmbH. All rights reserved.

light has protection against the ingress of dust and water and is tested for impact resistance in accordance with IK06. This inspection light has an integrated hook and magnets for hands-free work, making it ideal as a light for manual tasks, car repairs and for everyday use. In addition, OSRAM grants a 2-year guarantee on this product*

© 2026, OSRAM GmbH. All rights reserved.

Product datasheet

Technical data

Product information

Application (Category and Product specific)	LED inspection lights

General Product Information

Global order reference	LEDIL410

Electrical Data

Nominal wattage	9 W
Nominal voltage	3.7 V

Photometric Data

Color temperature	6000 K
Nominal luminous flux	1000 lm
Light color LED	White

Physical Attributes & Dimensions



Product weight	340.00 g
Length	365.0 mm
Width	50.0 mm
Height	50.0 mm

LED module information

Number of LEDs per module	2

Colors & materials

Base color	Black / Orange

© 2026, OSRAM GmbH. All rights reserved.

Lifetime Data

Guarantee	2 years

Additional product data

Type of Battery	Rechargeable
Number of included batteries	1
Scope of battery	Yes
Battery	High-quality lithium-ion battery

Capabilities

Technology	LED

Certificates & standards

Standards	CE / EMC / MSDS / ROHS
IK Class	IK06

Logistical data

Watt hour per battery	9.49

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)	
Candidate list substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe use instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration no. in SCIP database	99d5749d-0f33-4ebf-9ff7-b17da405d236

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172355674	INSPECTION LAMP	Folding carton box 1	72 mm x 60 mm x 370 mm	1.60 dm^3	409.00 g
4062172355681	INSPECTION LAMP	Shipping carton box 6	390 mm x 165 mm x 150 mm	9.65 dm^3	2678.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

© 2026, OSRAM GmbH. All rights reserved.

Product datasheet

Download Data

	File
	User instruction GPRS_Safety symbols instructions

Legal advice
Application advice:

For more detailed application information and graphics please see product datasheet and user instruction.*for precise conditions please refer to:

www.osram.com/am-guarantee

Application advice
For more detailed application information and graphics please see product datasheet.

Disclaimer
Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2026, OSRAM GmbH. All rights reserved.