

LEDinspect SLIM MAX1000

Inspectionlights



Dimmer Switch

Individually adjustable brightness levels with up to 1000 lm



1000 Lumen

Bright, white LED light and uniform light distribution



Multi-Angle Light Output

High flexibility due to individual adjustment of the light beam



2-year-OSRAM guarantee*

Systematic quality assurance measures underpin the premium workmanship and functionality of our products. Innovative technology and excellent quality really pay dividends for our customers.

Product datasheet



Light is versatile

This high-quality inspection light is perfect for professional and private use. With an integrated dimmer, you can select the appropriate brightness level with up to 1000lm for the task at hand with the SLIM MAX 1000. The ultra slim design combined with multi-angle positioning gives maximum flexibility and adjustability to give light exactly where needed. The SLIM MAX 1000 is rechargeable and cordless with Li-ion battery and can therefore provide constant light output. The lamp has an operating time of up to 1.5h with high light output or up to 10,5h with low light output. Charging cable and mains adaptor are included in the scope of supply. In accordance with the IP protection class IP65, this inspection light has protection against the ingress of dust and water and is tested for impact resistance in accordance with IK06. This inspection light has an integrated hook and magnets for hands-free work, making it ideal as a light for manual tasks, car repairs and for everyday use. In addition, OSRAM grants a 2-year guarantee on this product*

Product datasheet

Technical data

Product information

Application (Category and Product specific)	LED inspection lights
---	-----------------------

General Product Information

Global order reference	LEDIL410
------------------------	----------

Electrical Data

Nominal wattage	9 W
Nominal voltage	3.7 V

Photometric Data

Color temperature	6000 K
Nominal luminous flux	1000 lm
Light color LED	White

Physical Attributes & Dimensions

Product weight	340.00 g
Length	365.0 mm
Width	50.0 mm
Height	50.0 mm

LED module information

Number of LEDs per module	2
---------------------------	---

Colors & materials

Base color	Black / Orange
------------	----------------

Lifetime Data

Guarantee	2 years
-----------	---------

Additional product data

Type of Battery	Rechargeable
Number of included batteries	1
Scope of battery	Yes
Battery	High-quality lithium-ion battery

Capabilities

Product datasheet

Technology	LED
------------	-----

Certificates & standards

Standards	CE / EMC / MSDS / ROHS
IK Class	IK06

Logistical data

Watt hour per battery	9.62
-----------------------	------

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of declaration	26-06-2024
Candidate list substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe use instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration no. in SCIP database	99d5749d-0f33-4ebf-9ff7-b17da405d236

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172355681	INSPECTION LAMP		- x - x -	9.65 dm ³	

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Legal advice

Application advice:

For more detailed application information and graphics please see product datasheet and user instruction.*for precise conditions please refer to:

www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

