


## BA-S-CP-830-24 -G5

BackLED S CP G5 | LED modules for light advertising and backlighting



### Product family features

- Each LED module contains 2 LEDs
- Compatible with OSRAM OPTOTRONIC constant voltage drivers / dimmers
- Color consistency in 3 SDCM
- Patented Square Lens technology
- Wide CCT options available
- IP66 rating
- Lifetime (L80/B10): 50,000 h (temperature at  $T_c = 70\text{ °C}$ )

### Product family benefits

- Backside injection technology for high protection level
- 5 year guarantee

### Areas of application

- Channel letters
- Signage boxes
- Luminous areas and ceilings



# Product datasheet

## Technical data

### Electrical data

Nominal voltage	24.0 V
Nominal wattage per chain	24.00 W
Nominal wattage per LED module	0.3 W
Accidental reverse input voltage protection up to	25 V
Input voltage range	23.4...24.9 V
Type of current	DC

### Photometrical data

Color temperature	3000 K
Color rendering index Ra	80
Light color (designation)	Warm White
Light color LED	Warm white
Luminous flux per module chain	3440 lm
Luminous flux per LED module	43 lm
Luminous efficacy	143 lm/W
Standard deviation of color matching	≤3 sdcn



### Light technical data

Beam angle	155 °
------------	-------

### LED module information

Number of LEDs per module	2
Number of LED modules per chain	80
Minimum operable number of LED modules	1

### Dimensions & weight



## Product datasheet

Length	10935 mm
Width	12.2 mm
Height	10.3 mm
Product weight	425.00 g

### Temperatures & operating conditions

Temperature range in operation at Tc point	-25...70 °C
Temperature range at storage	-25...85 °C

### Lifespan

Lifespan	50000 h <sup>1)</sup>
----------	-----------------------

<sup>1)</sup> L80/B10 at Tc 70°C

### Additional product data

Product remark	Modules perfectly matched to OSRAM OPTOTRONIC LED drivers (see relevant table)/For current photometric data and important safety, installation and application information (see <a href="http://www.osram.com/led-systems">www.osram.com/led-systems</a> )./In view of the complex manufacturing process for light emitting diodes, the typical values given above for the technical LED parameters are merely statistical values that do not necessarily correspond to the actual technical parameters of an individual product; individual products may vary from the typical values
ID of contained light source	LS_SHZ_600832

### Capabilities

Dimmable	Yes
Dimming range	1...100 %

### Certificates & standards

Energy consumption	24 kWh/1000h
Type of protection	IP66
Standards	IEC/EN 60529/IEC/EN 60598-1/IEC/EN 61347-1/IEC/EN 61547/IEC/EN 62031/IEC/TR 62778/IEC TR 62778
Approval marks – approval	CE / BIS / cURus / ENEC 25 / UKCA
Energy efficiency class of the contained light source	E

### Logistical data

Commodity code	85395100000
----------------	-------------

## Product datasheet








### Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	31-03-2023
Primary Article Identifier	4052899627994
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	No declarable substances contained

### Additional product information

- Installation of LED modules (with power supplies) needs to be made under consideration of all valid regulations and norms.
- Installation by qualified electrician only.
- Please see the relevant application guides and instructions sheets for more detailed safety and mounting information. Additional information is available on request.

### Download Data

File	
	User instruction BackLED CP G5 User Instruction 20210730
	Product Datasheet product datasheet BackLED S CP 24V G5
	Brochures Technical application guide BackLED and BoxLED portfolio (EN)
	Certificates ENEC of BackLED CP G5
	Certificates UL certificate of Compliance BackLED CP G5
	CAD data 3-dim 3D drawing of BackLED CP 24V G5 MHOHFS
	IES data IES file of BA S CP 830 24 G5

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899627994	BA-S-CP-830-24 -G5	Shipping carton box 20	355 mm x 255 mm x 240 mm	21.73 dm <sup>3</sup>	9220.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## Product datasheet

---

### Accessories Optional

Product description	Accessory name	Accessory code
BA-S-CP-830-24 -G5	BA -MP-SM-G5-2M	▶ 4052899629196
BA-S-CP-830-24 -G5	BA -CLIP-SM-G5	▶ 4052899629349

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.