

LEDDriving SL T5

Ideal replacement for any vehicle




Suitable for various vehicle interior and exterior applications

Available in Cool White



Replaces conventional T5 lamps (e.g. ECE W2.3W)

Easy upgrade to LED technology with plug & play solutions



Reliable OSRAM quality stands for less lamp replacements

4-year guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for T5 (e.g. W2.3W)

LEDDriving SL T5 replacement lamps offer a modern and intense light with a color temperature up to 6,000 Kelvin. These replacement lamps are suitable for all conventional T5 lamp bases (e.g. ECE W2.3W). In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product datasheet

Technical data

Product information

Product type (off-road vs. on-road)	Off-road \triangleq W2.3W (T5)
Application (Category and Product specific)	Mainly used for signal/ indicator applications

General Product Information

Global order reference	2723DWP
------------------------	---------


Electrical Data

Power input	0.25 W
Nominal voltage	12.0 V
Nominal wattage	0 W
Test voltage	13.5 V
Power input tolerance	± 20 %

Photometric Data

Nominal luminous flux	25 lm
Luminous flux tolerance	± 25 %
Color temperature	6000 K
Light color LED	Cool white

Physical Attributes & Dimensions



Diameter	6 mm
Product weight	0.35 g
Length	16.5 mm
Lamp base	W2x4.6d

Lifetime Data

Product datasheet

Lifespan B3	750 hr
Lifespan Tc	2000 hr
Guarantee	4 years

Capabilities

Technology	LED ¹⁾
------------	-------------------

¹⁾ Light-emitting diode lamp

Environmental & Regulatory Information


Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of declaration	16-09-2024
Primary article identifier	4062172254687 4062172401838
Declaration no. in SCIP database	In work

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172254687	LEDiving SL \triangleq W2.3W (T5)	Blister 2	135 mm x 95 mm x 8 mm	0.10 dm ³	12.00 g
4062172254694	LEDiving SL \triangleq W2.3W (T5)	Shipping carton box 10	104 mm x 71 mm x 146 mm	1.08 dm ³	93.00 g
4062172401838	LEDiving SL \triangleq W2.3W (T5)	Blister 2	95 mm x 17 mm x 135 mm	0.22 dm ³	12.00 g
4062172401845	LEDiving SL \triangleq W2.3W (T5)	Shipping carton box 10	142 mm x 64 mm x 104 mm	0.95 dm ³	83.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

File
 Brochures LEDiving Retrofits - Exchange overview (EN)

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product datasheet

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

The OSRAM logo is displayed in a bold, orange, sans-serif font.