

# LEDDriving SL T5

Ideal replacement for any vehicle



**Suitable for various vehicle interior and exterior applications**

Available in Cool White



**Replaces conventional T5 lamps (e.g. ECE W2.3W)**

Easy upgrade to LED technology with plug & play solutions

**Reliable OSRAM quality stands for less lamp replacements**

4-year guarantee (refer to [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee) for precise conditions)



## **Suitable LED replacement for T5 (e.g. W2.3W)**

LEDDriving SL T5 replacement lamps offer a modern and intense light with a color temperature up to 6,000 Kelvin. These replacement lamps are suitable for all conventional T5 lamp bases (e.g. ECE W2.3W). In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Technical data

Product information

|   |  |
|---|--|
| Order reference                             | 2723DWP  |
| Product type (off-road vs. on-road)         | Off-road $\pm$ W2.3W (T5)                      |
| Application (Category and Product specific) | Mainly used for signal/ indicator applications |


Electrical data

|                       |            |
|-----------------------|------------|
| Power input           | 0.25 W     |
| Nominal voltage       | 12.0 V     |
| Nominal wattage       | 0.25 W     |
| Test voltage          | 13.5 V     |
| Power input tolerance | $\pm 20$ % |

Photometrical data

|                         |            |
|-------------------------|------------|
| Luminous flux           | 25 lm      |
| Luminous flux tolerance | $\pm 25$ % |
| Color temperature       | 6000 K     |
| Light color LED         | Cool white |

Dimensions & weight



|                |         |
|----------------|---------|
| Diameter       | 6 mm    |
| Product weight | 0.35 g  |
| Length         | 16.5 mm |

Lifespan

|             |         |
|-------------|---------|
| Lifespan B3 | 750 h   |
| Lifespan Tc | 2000 h  |
| Guarantee   | 4 years |

Product datasheet

Additional product data

|                             |         |
|-----------------------------|---------|
| Base (standard designation) | W2x4.6d |
|-----------------------------|---------|

Capabilities

|            |                   |
|------------|-------------------|
| Technology | LED <sup>1)</sup> |
|------------|-------------------|

<sup>1)</sup> Light-emitting diode lamp

Country specific categorizations

|                 |         |
|-----------------|---------|
| Order reference | 2723DWP |
|-----------------|---------|

Environmental information


| Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) |                               |
|---|-------------------------------|
| Date of Declaration   | 07-03-2024                    |
| Primary Article Identifier  | 4062172254687   4062172401838 |
| Declaration No. in SCIP database                                      | In work                       |

Logistical Data

| Product code  | Product description          | Packaging unit<br>(Pieces/Unit) | Dimensions (length<br>x width x height) | Volume               | Gross weight |
|---------------|------------------------------|---------------------------------|---|----------------------|--------------|
| 4062172254687 | LEDriving SL ≙<br>W2.3W (T5) | Blister<br>2                    | 135 mm x 95 mm x<br>8 mm                | 0.10 dm <sup>3</sup> | 12.00 g      |
| 4062172254694 | LEDriving SL ≙<br>W2.3W (T5) | Shipping carton box<br>10       | 104 mm x 71 mm x<br>146 mm              | 1.08 dm <sup>3</sup> | 93.00 g      |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

| File  |   |
|---|---|
|  | Brochures<br>LEDriving Retrofits - Exchange overview (EN) |

**Legal advice**

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

**Application advice**

## Product datasheet

For more detailed application information and graphics please see product datasheet.

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

# OSRAM