Product datasheet

LEDriving SL R10W

Ideal replacement for any vehicle

Suitable for various vehicle interior and exterior applications
Available in Cool White

Reliable OSRAM quality stands for less lamp replacements
4-year guarantee (refer to www.osram.com/am-guarantee for precise conditions)

Suitable LED replacement for R10W

LEDriving SL R10W replacement lamps offer a modern and intense light with a color temperature up to 6,000 Kelvin. These replacement lamps are suitable for all conventional R10W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDriving SL lamps.These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

© 2026, OSRAM GmbH. All rights reserved.

Product datasheet

Technical data

Product information

Product type (off-road vs. on-road)	Off-road ≙ R10W
Application (Category and Product specific)	Mainly used for signal/ indicator applications

General Product Information

Global order reference	5008DWP

Electrical Data

Power input	1.24 W
Nominal voltage	12 V
Nominal wattage	1 W
Power input tolerance	±20 %
Test voltage	13.5 V

Photometric Data

Color temperature	6000 K
Nominal luminous flux	125 lm
Luminous flux tolerance	±25 %
Light color LED	Cool white

Physical Attributes & Dimensions



Lamp base	BA15s
Length	37.5 mm
Diameter	19.0 mm
Product weight	9.80 g

Lifetime Data

© 2026, OSRAM GmbH. All rights reserved.

Product datasheet

Lifespan B3	1500 hr
Lifespan Tc	4000 hr
Guarantee	4 years

Capabilities

Technology	LED [1)]

[1)] Light-emitting diode lamp

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)	
Primary article identifier	4062172222846 | 4062172222822 | 4062172401296
Candidate list substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe use instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration no. in SCIP database	acfdb47e-fe18-4536-a610-cbb4826f1ca3 | 785bd7fd-0d7a-4942-b9cd-6c9b06b40981 | ae611627-677a-439a-bb49-72f598538ea1

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172401296	LEDriving SL ≙ R10W	BLI ECO 2	95 mm x 27 mm x 135 mm	0.35 dm^3	32.00 g
4062172401302	LEDriving SL ≙ R10W	Shipping carton box 10	142 mm x 104 mm x 104 mm	1.54 dm^3	192.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

	File
	User instruction GPRS_Safety symbols instructions
	Brochures LEDriving Retrofits - Exchange overview (EN)

Safety advice

© 2026, OSRAM GmbH. All rights reserved.

Canbus compatible

Legal advice
These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice
For more detailed application information and graphics please see product datasheet.

Disclaimer
Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2026, OSRAM GmbH. All rights reserved.