

Данные о продуктовой линейке

## TYREinflate Connect 650



### Download via App

The smart app stores the tyre pressure for your car and downloads it to the OSRAM TYREinflate Connect 650



### Auto Stop function

Auto Stop function when pre-set pressure is reached.



### Leak Detection

Including function to detect a loss of tyre pressure



### OSRAMconnect

Connecting you with your car



### OSRAMconnect App compatible tyre inflator

Improve your driving performance and fuel costs by making sure your tyre pressure is correct. The OSRAM TYREinflate Connect 650 is a digital tyre inflator compatible with the OSRAMconnect app, with a backlit display for easy and accurate pressure measurement and inflation<sup>3)</sup> of tyres, showing pressure values in BAR, kPA and PSI. The app can store up to 5 vehicles and their associated information, has active reminder functions and a leak detection function. Furthermore, the OSRAM TYREinflate Connect 650 has an automatic switch-off function as soon as the preset pressure is reached. In addition, it has a storage compartment for valve caps, a 3.3 m long retractable power cable with a 12V fuse plug, a 65 cm long flexible air hose with an easily accessible holder and an additional LED light for illumination at night or in poor lighting conditions and a large on/off switch for additional manual operation. An inflation time of about 3 minutes<sup>2)</sup> gets you on the road and where you need to be fast. Also included is a 3-piece adapter set, for bikes, balls and other inflatables, and a durable storage bag. OSRAM provides a 2-year guarantee on this product<sup>1)</sup>

<sup>1)</sup> For precise conditions please refer to: [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)

<sup>2)</sup> Based on inflating a 13" tyre from flat to 2.41 BAR

<sup>3)</sup> Measurements of the tyre pressure and inflation of the tyres to the optimum tyre pressure must always be conducted on cold tyres


Данные о продуктовой линейке

Technical data

	Электрические параметры	Дополнительные данные	Возможности / мощности	Нормативная и природоохранная информация <b>Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)</b>
Описание продукта	Номинальное напряжение	Тип дисплея	Предохранитель	Основной идентификатор изделия
TYRE inflate Connect 650	11.1 V	Digital	10 A	4052899622883

Описание продукта	Список компонентов вещество 1	CAS-номер вещества 1	Инструкция по безопасному использованию	Номер декларации в базе данных <b>SCIP</b>
TYRE inflate Connect 650	Lead	7439-92-1	Идентификация вещества из списка компонентов достаточна для безопасного использования изделия.	f2f01f10-b494-4e57- ad3c-e7f344875985

Загрузка данных

Файл	
	User instruction TYREinflate Connect 650

Советы по безопасности

Достигает максимального уровня шума 90 дБ.

Соответствие стандартам

- 1) For precise conditions please refer to: [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)
- 2) Based on inflating a 13" tyre from flat to 2.41 BAR
- 3) Measurements of the tyre pressure and inflation of the tyres to the optimum tyre pressure must always be conducted on cold tyresApplication advice:For more detailed application information and graphics please see product datasheet and the user instruction.

Рекомендации по применению

Для получения дополнительной информации и изображения продукции, пожалуйста, ознакомьтесь с инструкцией.

Примечание

В заказ могут быть внесены изменения без предварительного уведомления. Проверьте информацию на наличие ошибок. Убедитесь, что информация актуальна.