Product family datasheet

TYREinflate Connect 650

Download via App
The smart app stores the tyre pressure for your car and downloads it to the OSRAM TYREinflate Connect 650

Auto Stop function
Auto Stop function when pre-set pressure is reached.

Leak Detection
Including function to detect a loss of tyre pressure

OSRAMconnect
Connecting you with your car



OSRAMconnect App compatible tyre inflator

Improve your driving performance and fuel costs by making sure your tyre pressure is correct. The OSRAM TYREinflate Connect 650 is a digital tyre inflator compatible with the OSRAMconnect app, with a backlit display for easy and accurate pressure measurement and inflation3) of tyres, showing pressure values in BAR, kPA and PSI. The app can store up to 5 vehicles and the associated information and has a function to detect a loss of tyre pressure. Furthermore, the OSRAM TYREinflate Connect 650 has an automatic switch-off function as soon as the preset pressure is reached. In addition, it has a storage compartment for valve caps, a 3.3 m long retractable power cable with a 12V fuse plug, a 65 cm long flexible air hose with an easily accessible holder and an additional LED light for illumination at night or in poor lighting conditions and a large on/off switch for additional manual operation. An inflation time of about 3 minutes2) gets you on the road and where you need to be fast. Also included is a 3-piece adapter set, for bikes, balls and other inflatables, and a durable storage bag. OSRAM provides a 2-year guarantee on this product1)1) For precise conditions please refer to: www.osram.com/am-guarantee2) Based on inflating a 13” tyre from flat to 2.41 BAR3) Measurements of the tyre pressure and inflation of the tyres to the optimum tyre pressure must always be conducted on cold tyres

© 2024, OSRAM GmbH. All rights reserved.

Product family datasheet

Technical data

	Electrical data	Dimensions & weight			Additional product data	Capabilities
Product description	**Nominal voltage**	**Height**	**Width**	**Length**	**Display Type**	**Fuse**
TYRE inflate Connect 650	11.1 V	219.0 mm	90.0 mm	200.0 mm	Digital	10 A

	Country specific categorizations	Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)		
Product description	**Order reference**	**Date of Declaration**	**Primary Article Identifier**	**Declaration No. in SCIP database**
TYRE inflate Connect 650	OTIC650	07-03-2024	4052899622883	In work

© 2024, OSRAM GmbH. All rights reserved.

Product family datasheet

Download Data

	File
	User instruction TYREinflate Connect 650

Safety advice
Reaches a maximum noise level of 90 db.

Legal advice
1) For precise conditions please refer to: www.osram.com/am-guarantee

2) Based on inflating a 13” tyre from flat to 2.41 BAR

3) Measurements of the tyre pressure and inflation of the tyres to the optimum tyre pressure must always be conducted on cold tyres

Application advice:For more detailed application information and graphics please see product datasheet and the user instruction.

Application advice
For more detailed application information and graphics please see product datasheet.

Disclaimer
Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2024, OSRAM GmbH. All rights reserved.