


LEDDriving HL EASY XEN D1S



Easy plug & play installation

Accurate mechanical compatibility – no adapters and/or caps needed



Compact LED replacement for conventional high and low beam lamps

Same geometry as HID - allowing high compatibility with plenty of car models



Cool White color temperature of 6,500 K

Better visibility thanks to daylight effect



OSRAM's first Plug & Play off-road LED replacement for HID

With extra brightness the OSRAM LEDDriving HL EASY XEN ensures a compact LED replacement of conventional high and low beam lamps. These LED retrofit lamps are 12/24V compatible, come with a color temperature of 6,500 K and ensure a broader light distribution: more light allows to see better and therefore react sooner. The top OSRAM thermal management technology with integrated active cooling – a high speed fan - provides maximized heat dissipation for more powerful performances. Premium OSRAM quality and LED technology grant a long lifetime.

Please note: OSRAM LEDDriving HL EASY XEN change is recommended to be carried out by a professional.

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Technische Daten

Produkt-Bezeichnung	Elektrische Daten				Photometrische Daten
	Max. Leistungsaufnahme	Nennspannung	Nennleistung	Prüfspannung	Lichtstrom
LEDriving HL EASY XEN $\pm$ D1S	40 W	12 V	40 W	13,2 V	5000 lm

Produkt-Bezeichnung	Lichtstrom-Toleranz	Physical Attributes & Dimensions	Lebensdauer	Umwelt Informationen Informationen gemäß Art. 33 der EU Richtlinie (EC) 1907/2006 (REACH)	
		Durchmesser	Lebensdauer Tc	Primäre Erzeugnisnummer	Stoff der Kandidatenliste 1
LEDriving HL EASY XEN $\pm$ D1S	$\pm$ 25 %	13.8 mm	5000 hr	4062172421447	Kein deklarationspflichtiger Stoff enthalten

Produkt-Bezeichnung	SCIP Deklarationsnummer
LEDriving HL EASY XEN $\pm$ D1S	Kein deklarationspflichtiger Stoff enthalten

Downloads

Datei	
	User instruction GPRS_Sicherheitssymbole Benutzerhinweise

Anwendungshinweis

Für weitere Anwendungsinformationen beachten Sie bitte das Produktdatenblatt.

Haftungsausschluss

Änderungen und Irrtümer vorbehalten. Vergewissern Sie sich, dass Sie immer den neuesten Stand verwenden.

