Product family datasheet

LEDriving HL EASY GEN 2 H15

Ultra compact LED replacement for conventional high and low beam lamps

"Socket Design" – no adapters and caps needed

Easy plug & play installation

Allowing a high compatibility and an easy installation

Cool White color temperature

Better visibility thanks to daylight effect

LED high and low beams lamps with plug & play system: no adapters and caps needed

With its socket-based solution, the OSRAM LEDriving HL EASY GEN 2 retrofits provide an ultra-compact LED replacement of conventional high and low beam lamps with cool white LED light – providing a stylish look as well as superior brightness. It offers an easy plug & play installation with optimized compatibility: no adapters and caps needed! An optimized high-speed fan ensures active cooling – making a higher performance and high-level light output possible thanks to maximized heat dissipation.

The LEDriving HL EASY GEN 2 high and low beam lamps by OSRAM replace conventional halogen lamps, are 12V compatible and have a cool white color temperature. With the latest LED technology and very compact design, these lamps allow a high compatibility and an easy installation for cars with the respective halogen lamp types. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

© 2026, OSRAM GmbH. All rights reserved.

Product family datasheet

Technical data

	Electrical Data			Photometric Data		Physical Attributes & Dimensions
Product description	**Power input**	**Nominal voltage**	**Test voltage**	**Nominal luminous flux**	**Luminous flux tolerance**	**Diameter**
LEDriving HL EASY ≙ H15	23 / 4 W	12 V	13.2 V	1250/250 lm	±25 %	15.8 mm

	Lifetime Data	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)	
Product description	**Lifespan Tc**	**Primary article identifier**	**Declaration no. in SCIP database**
LEDriving HL EASY ≙ H15	1000 hr	4062172426442	In work

© 2026, OSRAM GmbH. All rights reserved.

Download Data

	File
	User instruction GPRS_Safety symbols instructions

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2026, OSRAM GmbH. All rights reserved.