

LEDiving ERROR CANCELER

Accessories for LED retrofit lamps



Error message free

Bypasses the vehicle's error detection



Flicker-free

Prevents additional irritating flashing of the LED lamps



3-year OSRAM Guarantee²⁾

Systematic quality assurance measures underpin the premium workmanship and functionality of our products.

Innovative technology and excellent quality really pay dividends for our customers.



Duopack

Two Error canceler in one box



Convert from halogen to LED with original OSRAM accessories

Some vehicles report a malfunction in the exterior lighting when LED lamps are used. With the new OSRAM LEDiving ERROR CANCELER LED EC02, potential error messages in the on-board system are avoided. These error messages can occur when converting from traditional halogen lamps to LED lamps as these have a lower current consumption than e.g. halogen lamps and thus activate the vehicle's existing error detection mechanism. Furthermore, OSRAM's new and improved LEDiving ERROR CANCELER LED EC02 prevents irritating LED lamp flashing. It is suitable for 12V H7 LED lamps for high and low beam. In addition, OSRAM offers a three-year OSRAM guarantee²⁾ on all accessories in the LEDiving series. Only the combination of OSRAM LED lamps in conjunction with the official OSRAM accessories - LEDiving ADAPTER, LEDiving SMART CANBUS, LEDiving CAPs and LEDiving ERROR CANCELER is approved for the operation of our LED lamps. Details, in particular on the combination of OSRAM accessories and the street-legal¹⁾ NIGHT BREAKER LED and TRUCKSTAR LED lamps, can be found on the respective product pages under: NIGHT BREAKER LED Kompatibilitätslisten | Automotive (osram.de)



Product family datasheet

Technical data

| | Electrical Data | Lifetime Data | | Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) | |
|--|-----------------|----------------|----------------|--|-------------------------------|
| Product description | Nominal wattage | Lifespan B3 | Lifespan Tc | Primary article identifier | Candidate list substance 1 |
| LEDDriving ERROR CANCELER LEDEC02-2HB | 1.00 W | 2500 hr | 2500 hr | 4062172383721 | Lead |

| Product description | CAS No. of substance 1 | Safe use instruction | Declaration no. in SCIP database |
|--|---------------------------|---|--|
| LEDDriving ERROR CANCELER LEDEC02-2HB | 7439-92-1 | The identification of the Candidate List substance is sufficient to allow safe use of the article. | bdd31784-c584- 41b0-b49e- e218e7d29151 |

Download Data

| File | |
|---|--|
|  | User instruction LEDriving ERROR CANCELER LEDEC02 |
|  | User instruction GPRS_Safety symbols instructions |

Safety advice

Application advice:For more detailed application information and graphics please see product datasheet and user manual.

Legal advice

1) Approved LED light source applies to all vehicle models to specific light functions and further restrictions in the respective country. Must not be used behind red and/or yellow colored glass.

For more details see www.osram.com/nb-led2) For precise conditions please refer to: www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.