

LEDDriving HL INTENSE H7/H18



Up to +350% more brightness

More light allows to see farther and therefore react sooner. Signs, obstacles and hazards can be recognized sooner. Compared to minimum ECE R112



Very compact LED replacement for conventional H7/H18 high and low beam lamps (2in1)

Reduced glaring thanks to an optimized light distribution



Cool White color temperature of 6,000 K

Better visibility thanks to daylight effect



5-year OSRAM guarantee

For precise conditions, please refer to www.osram.com/am-guarantee



OSRAM's highest performing LED off-road retrofit lamp

With up to +350% more brightness (compared to ECE R112) and a very compact LED replacement of conventional H7/H18 and H4/H19 high and low beam lamps, the LEDDriving HL INTENSE is OSRAM's highest performing LED off-road retrofit lamp ever! This LED retrofit lamp offers OSRAM top technology beam pattern as well as an easy installation with a wide OSRAM range of suitable accessories. Top thermal management technology with integrated active cooling – a high speed fan ensures maximized heat dissipation for more powerful performances. Also premium OSRAM quality, manufactured in a certified OSRAM production plant in Italy, and a 5-year guarantee as well as a long service life. For precise guarantee conditions please refer to www.osram.com/am-guarantee. The LED high and low beam lamps by OSRAM replace conventional halogen lamps, are 12V compatible and have a color temperature of 6,000K. With the latest LED technology and very compact design, these lamps allow a high compatibility and an easy installation for an even wider range of car models. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Technical data

Product information

Order reference	64210DWINT
Product type (off-road vs. on-road)	Off-road \triangleq H7/H18
Application (Category and Product specific)	Mainly used for Low Beam, High Beam


Electrical data

Power input	22.0 W
Nominal voltage	12.0 V
Nominal wattage	21.00 W
Test voltage	13.2 V
Power input tolerance	$\pm 15\%$

Photometrical data

Luminous flux	2000 lm
Luminous flux tolerance	$\pm 20\%$
Color temperature	6000 K
Light color LED	Cool white

Dimensions & weight



Length	81.3 mm
Diameter	13.8 mm
Product weight	56.00 g

Lifespan

Lifespan Tc	5000 h
Guarantee	5 years

Product datasheet

Capabilities

Technology	LED
------------	-----

Country specific categorizations

Order reference	64210DWINT
-----------------	------------

Environmental information



Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	08-03-2024
Primary Article Identifier	4062172306430
Declaration No. in SCIP database	In work

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172306430	LEDiving HL INTENSE ≙ H7/H18	Folding carton box 2	136 mm x 56 mm x 162 mm	1.23 dm³	184.00 g
4062172306447	LEDiving HL INTENSE ≙ H7/H18	Shipping carton box 8	240 mm x 148 mm x 182 mm	6.46 dm³	862.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

File	
	User instruction LEDiving HL INTENSE
	Brochures LEDiving Retrofits - Exchange overview (EN)

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

