OSRAM

LEDriving HL BRIGHT H8/H11/H16



Up to +300% more brightness

More light allows to see

farther and therefore react

sooner. Signs, obstacles and

hazards can be recognized sooner. Compared to minimum ECE R112, for H7/H18 & H4/H19



Very compact LED replacement for conventional H8H11H16H9 high and low beam lamps

Reduced glaring thanks to an optimized light distribution



Cool White color temperature of 6,000 K



4 year OSRAM guarantee

Better visibility thanks to daylight effect

For precise conditions, please refer to www.osram.com/am-guarantee





High-performing LED retrofit lamp providing improved visibility and a stylish look

With up to +300% more brightness (compared to ECE R112, for H7/H18 & H4/H19), the OSRAM LEDriving HL BRIGHT retrofit lamp ensures optimum visibility and thus allowing drivers to recognize signs, obstacles and hazards sooner than conventional lamps. This LED retrofit lamp not only creates a stylish modern look with a cool white color temperature of 6,000K but also offers reduced glaring thanks to an optimized light distribution. Premium OSRAM quality and LED technology grant up to 5 times more lifetime (compared to ECE R112) and better visibility thanks to daylight effect. The pair of lamps comes with a 4-year OSRAM guarantee. For precise quarantee conditions please refer to www.osram.com/am-guarantee.The LEDriving HL BRIGHT high and low beam lamps by OSRAM replace conventional halogen lamps and are 12V compatible. With the latest LED technology and very compact design, these lamps allow a high compatibility and an easy installation for cars with the respective halogen lamp types. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data

	Product information				Electrical data			
Product description	Order reference	Product type (off- road vs. on-road)	Application (Category and Product specific)			Nominal voltage	Nominal wattage	
LEDriving HL BRIGHT ≙ H8/H11/H16	64211DWB RT	Off-road ≙ H8/H11/H1 6/H9						
	Photometrical data		Dimensions & weight	Lifespan	Capabilitie	inform Inform accord EU Reg	Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)	
Product description	Luminous flux	Luminous flux tolerance	Diameter	Lifespan Tc	Technolog	y Date o	f Declaration	
LEDriving HL BRIGHT	1900 lm	±20 %	140 mm	5000 h	LED	29-03-	2024	

Product description	Primary Article Identifier	Declaration No. in SCIP database
LEDriving HL BRIGHT = H8/H11/H16	4062172315951	In work

Product family datasheet

Download Data

File



User instruction LEDriving HL BRIGHT



Brochures

LEDriving Retrofits - Exchange overview (EN)

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.











