TFP2000S-G1 -940-04

TEC FLEX Shortpitch Protect | LED modules for semi-professional applications



Product family features

- Flexible and cuttable LED strip
- Luminous flux: up to 2,000 lm/m
- Available with color temperature: 2,700K, 3,000 K, 4,000 K
- Up to 50,000 hrs lifetime @ tc max
- Recommended in system use with OPTOTRONIC
- Color consistency in 3 SDCM

Product family benefits

- High homogeneity thanks to small LED pitch
- Pre-wired LED strip, simple and quick plug-and-play installation
- Easy mounting on many smooth surfaces thanks to self-adhesive tape at the back
- Type of protection: IP66
- Dimmable (with suitable PWM dimming methods)

© 2024, Inventronics GmbH. All rights reserved. Inventronics is a licensee of the OSRAM brand. OSRAM is a trademark of ams OSRAM.

Technical data


Electrical data


Nominal voltage	24.0 V
Type of current	DC
Rated wattage	69.20 W
Input voltage range	23…25 V
Accidental reverse input voltage protection up to	25 V

Photometrical data

Light color LED	White
Color rendering index Ra	90
Luminous efficacy	105.2 lm/W
Light color (designation)	4000 K
Color temperature	4000 K
Standard deviation of color matching	≤3 sdcm
Total useful luminous flux	7280 lm

Dimensions & weight





Length	4020 mm
Product weight	227.00 g
Cable cross-section, input side	0.5 mm²
Width	8.00 mm
Height	4.10 mm

Temperatures & operating conditions

Temperature range in operation at Tc point	-25…80 °C
Temperature range at storage	-30…85 °C

© 2024, Inventronics GmbH. All rights reserved. Inventronics is a licensee of the OSRAM brand. OSRAM is a trademark of ams OSRAM.

Additional product data

ID of contained light source	LS_SHZ_601084

Certificates & standards

Standards	CE/ENEC/EAC/SASO 2927:2019
Energy efficiency class of the contained light source	F

Logistical data

Commodity code	85395100000

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)	
Date of Declaration	11-01-2023
Primary Article Identifier	4062172268745
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	No declarable substances contained

Equipment / Accessories

- Simplified connection with optional matching CONNECTsystem
- Flexessories: a complete set of aluminum channels with diffusers and lenses
- Drivers and dimmers: wide selection of OPTOTRONIC 24 V DALI, DMX and BLE

Download Data

	File
	User instruction TEC Flex IP66
	Product Datasheet TEC Flex Shortpitch IP66 Product Datasheet (EN)
	Brochures Light is strong - Discover the versatile and flexible lighting system OSRAM 24V TEC Flex (EN)
	Certificates TFX ENEC 130520
	Declarations of conformity TECFlex CE 4210017 080823
	Eulumdat TFP2000S-G1-940 LTD 130122
	IES data TFP2000S-G1-940 IES 130122

© 2024, Inventronics GmbH. All rights reserved. Inventronics is a licensee of the OSRAM brand. OSRAM is a trademark of ams OSRAM.

Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer.In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer.Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172268745	TFP2000S-G1 -940-04	Shipping carton box 10	280 mm x 305 mm x 180 mm	15.37 dm^3	3244.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Accessories Optional

Product description	Accessory name	Accessory code
TFP2000S-G1 -940-04	ENDCAP -IP67 KIT 10PCS	4062172176552
TFP2000S-G1 -940-04	LTS-SLIMTRACK -2000 KIT 5 PCS	4062172207300
TFP2000S-G1 -940-04	FX-QMS-G1 -T45D19H19-300	4052899448667
TFP2000S-G1 -940-04	FX-QMS-G1 -TU15H6-300	4052899448865
TFP2000S-G1 -940-04	FX-QMS-G1 -TU15H6W3-300	4052899448889
TFP2000S-G1 -940-04	FX-QMS-G1 -TU16H12W3-300	4052899448988
TFP2000S-G1 -940-04	FX-QMS-G1 -TU16H12-300	4052899448964
TFP2000S-G1 -940-04	FX -SC08-G2-CT4PJ	4052899464858
TFP2000S-G1 -940-04	FX -SC08-G2--BTJ-IP54	4052899568853
TFP2000S-G1 -940-04	FX-DCS -G1-GL-25	4052899452244
TFP2000S-G1 -940-04	FX-QMS-G1 -TU16H12LS-300	4052899449046

© 2024, Inventronics GmbH. All rights reserved. Inventronics is a licensee of the OSRAM brand. OSRAM is a trademark of ams OSRAM.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2024, Inventronics GmbH. All rights reserved. Inventronics is a licensee of the OSRAM brand. OSRAM is a trademark of ams OSRAM.