Product family datasheet

LEDriving HLM EASY H4/H19

Ultra compact LED replacement for conventional H4/H19 high and low beam lamps (2in1)

"Socket Design" – no adapters and caps needed

Easy plug & play installation

Allowing a high compatibility and an easy installation.

Cool White color temperature

Better visibility thanks to daylight effect

LED high and low beams lamps with plug & play system for motorcycles.

With its socket-based solution, the OSRAM LEDriving HLM EASY retrofits provide an ultra-compact LED replacement of conventional H4/H19 high and low beam lamps with cool white LED light – providing a stylish look as well as superior brightness. It offers an easy plug & play installation with optimized compatibility. An optimized high-speed fan ensures active cooling – making a higher performance and high-level light output possible thanks to maximized heat dissipation.The LEDriving HLM EASY high and low beam lamps by OSRAM replace conventional halogen lamps, are 12V compatible and have a cool white color temperature. With the latest LED technology and very compact design, these lamps allow a high compatibility and an easy installation for motorcycles with the respective halogen lamp types. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

© 2026, OSRAM GmbH. All rights reserved.

Product family datasheet

Technical data

	Electrical Data			Photometric Data	
Product description	**Power input**	**Nominal voltage**	**Nominal wattage**	**Nominal luminous flux**	**Luminous flux tolerance**
LEDriving HLM EASY ≙ H4/H19	16.5W/16.5 W	12 V	19 W	1400/1100 lm	±25 %

	Physical Attributes & Dimensions	Lifetime Data	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)	
Product description	**Diameter**	**Lifespan Tc**	**Primary article identifier**	**Candidate list substance 1**
LEDriving HLM EASY ≙ H4/H19	21.5 mm	1000 hr	4062172399821 | 4062172321525	Lead

Product description	**CAS No. of substance 1**	**Safe use instruction**	**Declaration no. in SCIP database**
LEDriving HLM EASY ≙ H4/H19	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	b37dc721-98bb-4626-9bd8-5a2288767698 | 21ee7419-4eaf-4d6d-96b9-7d7968571c79

© 2026, OSRAM GmbH. All rights reserved.

Product family datasheet

Download Data

	File
	User instruction GPRS_Safety symbols instructions
	Brochures LEDriving Retrofits - Exchange overview (EN)

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2026, OSRAM GmbH. All rights reserved.