

# NIGHT BREAKER LED W5W CARSPECIFIC



## Universal Polarity

Installation independent of polarity possible



## 6000 Kelvin

Cool white color temperature



## Plug & Play

Quick and easy upgrade to LED technology with plug & play solution



## Street-Legal1)

The NIGHT BREAKER LED family - OSRAM's first street-legal1) LED retrofit lamps.



With the NIGHT BREAKER W5W-LED, OSRAM's first street legal1) W5W-LED replacement lamp is now on the market

With the street-legal1) NIGHT BREAKER W5W-LED you can now upgrade the function of your parking lights or position lights of your vehicle to state-of-the-art LED technology. These LED replacement lamps are suitable as a replacement for conventional W5W lamps and bases. They offer a modern and intense white light with a color temperature up to 6000 Kelvin and a light output of up to 70 lm. In comparison to standard lamps, such as halogen lamps, these LED retrofit lamps consume up to 80% less energy. With the plug & play solution and the universal polarity they can be installed quickly and easily and regardless of polarity. In combination with the NIGHT BREAKER H7-LED or H4-LED you can now get the full LED upgrade for your vehicle with perfectly tailored and designed LED lamps - for exterior1) and interior applications. The NIGHT BREAKER W5W LED can be used universally in the interior of your vehicle as a replacement light source. You can now replace your vehicle lamps with OSRAM's revolutionary NIGHT BREAKER LED retrofit lamps and experience trend-setting brightness with road approval1) Additionally, OSRAM offers a dedicated guarantee on all NIGHT BREAKER LED retrofit lamps2)

Product family datasheet

Technical data

Product information					Electrical data
Product description	Product legal advice 1	Product legal advice 2	Order reference	Application (Category and Product specific)	Nominal voltage
NIGHT BREAKER W5W LED	1)Approved LED light source - only applies to the respective countries in which there is approval or to which an equivalent approval applies and the vehicle models and light functions currently listed in the compatibility list. For more details see <a href="http://www.osram.com/nb-led">www.osram.com/nb-led</a>	2) For precise conditions please refer to: <a href="http://www.osram.com/am-guarantee">www.osram.com/am-guarantee</a>	2825DWNBC	Position light, Interior light	120 V

					Photometrical data		
Product description	Nominal wattage	Power input tolerance	Test voltage	Power input	Luminous flux tolerance	Light color LED	Luminous flux
NIGHT BREAKER W5W LED	100 W	±25 %	13.2 V	1 W	±25 %	Cool white	70 lm

		Dimensions & weight			Lifespan		Additional product data
Product description	Color temperature	Length	Diameter	Product weight	Lifespan B3	Lifespan Tc	Base (standard designation)
NIGHT BREAKER W5W LED	6000 K	254 mm	940 mm	170 g	1500 h	3000 h	W2.1x9.5d

		Capabilities	Certificates & standards	Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Product description	Technology	Standards	Date of Declaration		Primary Article Identifier
NIGHT BREAKER W5W LED	LED	ABG	12-03-2024		4062172352239   4062172353625

Product description	Declaration No. in SCIP database
NIGHT BREAKER W5W LED	In work

Download Data

File	
	Brochures LEDriving Retrofits - Exchange overview (EN)

Safety advice

Application advice:For more detailed application information and graphics please see product datasheet and user manual.

Legal advice

1) Approved LED light source - only applies to the respective countries in which there is approval or to which an equivalent approval applies and the vehicle models and light functions currently listed in the compatibility list. For more details see [www.osram.com/nb-led](http://www.osram.com/nb-led)

2)For precise conditions refer to: [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

