Product datasheet

Lightbar VX1250-CB DR SM

Single mount certified
For individual installation

Up to 410 m long beam
Improved far and near field illumination

Combo Beam
Designed for both: far-field and near-field illumination

IP & IK protection classes
Tested and validated in a DIN-certified environmental simulation laboratory regarding extreme external influences such as water, dust, shocks, impacts, heat, cold, permanent vibrations and many more

Powerful LED driving lights for off-road and on-road use

Considerable foresight on dark country roads, forest paths, off the beaten tracks, off-road and on-road- this can be achieved with the OSRAM LEDriving Lightbar VX1250-CB DR SM. With its 108 powerful, high-performance LEDs, the driving light has a range of up to 410 meters and thus offers the driver impressive foresight on-road and off-road. Even in dim light and reduced visibility due to external environmental influences, the driving light with up to 6000 Kelvin can provide conditions similar to daylight. The power package with up to 13700 lumens scores with highest optical efficiency and homogeneous light distribution. The driving light is characterised by its robust double-row design, providing users with impressive illumination. In addition, the lightbar comes with standard brackets for various mounting options: hanging, standing and side. Versatile applicable, it defies numerous environmental influences and, thanks to high-quality materials such as the aluminum housing and the stable polycarbonate lens, it is particularly light and at the same time robust and resistant. The driving light has been tested and validated with the IP-Protection Classes IP6K8 & IP6K9K in our DIN certified environmental simulation laboratory for extreme external influences regarding water, dust, impacts, heat, cold and permanent vibration. Whether on-road or off-road, the LEDriving Lightbar VX1250-CB DR SM is an effective and

© 2026, OSRAM GmbH. All rights reserved.

efficient addition to your vehicle and can be attached to cars, trucks, agricultural machinery, commercial vehicles, construction vehicles, caravans, off-road vehicles and quads[1)]. OSRAM provides a 2-year guarantee[2)].1) OSRAM LEDriving Driving Lights are approved according to ECE regulations and may therefore be installed and operated on public roads. Please note: Special installation regulations apply. In addition to ECE approval of the product, individual special requirements and legislation of the countries must be observed. 2) For precise conditions refer to: www.osram.com/am-guarantee

© 2026, OSRAM GmbH. All rights reserved.

Product datasheet

Technical data

Product information

Application (Category and Product specific)	Driving Light - Additional high beam application - central single mount

General Product Information

Global order reference	LEDDL127-CB DR SM

Electrical Data

Nominal wattage	138 W
Test voltage	13.2 V

Photometric Data

Nominal luminous flux	13700 lm
Color temperature	6000 K
Light distance at 1lx	410 m

Physical Attributes & Dimensions







Product weight	4200.00 g
Length	1272 mm
Width	60.0 mm
Height	74.0 mm

Lifetime Data

Lifespan Tc	> 5000 hr
Guarantee	2 years

Additional product data

© 2026, OSRAM GmbH. All rights reserved.

Connector to lamp	Open wire

Capabilities

Technology	LED [1)]

[1)] Light-emitting diode application

Certificates & standards

Approval marks – approval	E57 approval
Type of protection	IP6K8/IP6K9K
Standards	ECE R10, R149
ECE reference number	20 + 20

Logistical data

Commodity code	85122000900

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)	
Candidate list substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe use instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration no. in SCIP database	ca1bfecf-12f0-4059-9e59-b4c625e39dd3

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172365468	Lightbar VX1250-CB DR SM LEDDL127-CB DR SM	Folding carton box 1	1388 mm x 110 mm x 123 mm	18.78 dm^3	4682.00 g
4062172365475	Lightbar VX1250-CB DR SM LEDDL127-CB DR SM	Shipping carton box 2	1411 mm x 241 mm x 151 mm	51.35 dm^3	10344.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

	File

© 2026, OSRAM GmbH. All rights reserved.

	User instruction LEDriving Lightbar VX1250-CB DR SM LEDDL127 CB DR SM
	User instruction GPRS_Safety symbols instructions

Safety advice

For detailed application information, please refer to the product data sheet and the user instruction

Legal advice

1) OSRAM LEDriving Driving Lights are approved according to ECE regulations and may therefore be installed and operated on public roads. Please note: Special installation regulations apply. In addition to ECE approval of the product, individual special requirements and legislation of the countries must be observed.2) For precise conditions refer to: www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2026, OSRAM GmbH. All rights reserved.