OSRAM

Lightbar VX750-CB SR SM



Single mount certified
For individual installation



Up to 410 m long beam
Improved far and near field
illumination



Combo beam

Designed for both: far-field
and near-field illumination



IP & IK protection classes

Tested and validated in a DINcertified environmental simulation laboratory regarding extreme external influences such as water, dust, shocks, impacts, heat, cold, permanent vibrations and many more



Powerful LED driving lights for off-road and on-road use

Considerable foresight on dark country roads, forest paths, off the beaten tracks, off-road and on-road- this can be achieved with the OSRAM LEDriving Lightbar VX750-CB SR SM. With its 27 powerful, high-performance LEDs, the driving light has a range of up to 410 meters and thus offers the driver impressive foresight on-road and off-road. Even in dim light and reduced visibility due to external environmental influences, the driving light with up to 6000 Kelvin can provide conditions similar to daylight. The power package with up to 4600 lumens scores with highest optical efficiency and homogeneous light distribution. The driving light is characterised by its compact single-row design, ensuring a sleek appearance. In addition, the lightbar comes with standard brackets for various mounting options: hanging, standing and side. Versatile applicable, it defies numerous environmental influences and, thanks to high-quality materials such as the aluminum housing and the stable polycarbonate lens, it is particularly light and at the same time robust and resistant. The driving light has been tested and validated with the IP-Protection Classes IP6K8 & IP6K9K in our DIN certified environmental simulation laboratory for extreme external influences regarding water, dust, impacts, heat, cold and permanent vibration. Whether on-road or off-road, the LEDriving Lightbar VX750-CB SR SM is an effective and efficient addition to your vehicle and can be attached to cars, trucks, agricultural machinery, commercial vehicles, construction vehicles, caravans, off-road vehicles and quads1). OSRAM provides a 2-year guarantee2).1) OSRAM LEDriving Driving Lights are approved according to ECE regulations and may therefore be installed and operated on public roads. Please note: Special installation regulations apply. In addition to ECE approval of the product, individual special requirements and legislation of the countries must be observed. 2) For precise conditions refer to: www.osram.com/am-guarantee

Technical data

Product information

| Order reference | LEDDL124-CB SR SM | |
|---|---|--|
| Application (Category and Product specific) | Driving Light - Additional high beam application - central single mount | |


Electrical data


| Nominal wattage | 81.00 W |
|-----------------|---------|
| Test voltage | 13.2 V |


Photometrical data

| Luminous flux | 4600 lm |
|-----------------------|---------|
| Color temperature | 6000 K |
| Light distance at 1lx | 410 m |

Dimensions & weight







| Product weight | 1995.00 g |
|----------------|-----------|
| Length | 778.0 mm |
| Width | 67.0 mm |
| Height | 35 mm |

Lifespan

| Lifespan Tc | > 5000 h |
|-------------|----------|
| Guarantee | 2 years |

Additional product data

|--|

Capabilities

| Technology | LED ¹⁾ |
|------------|-------------------|
|------------|-------------------|

 $^{^{1)}}$ Light-emitting diode application

Certificates & standards

| Standards | ECE R10, R149 |
|---------------------------|---------------|
| Approval marks – approval | E57 approval |
| Type of protection | IP6K8/IP6K9K |
| ECE reference number | 25 + 25 |

Country specific categorizations

| Order reference | LEDDL124-CB SR SM |
|-----------------|-------------------|
| Order reference | LLUULIZT-CU SK SM |

Logistical data

| Commodity code | 85122000900 |
|----------------|-------------|

Environmental information

| Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh) | | |
|---|---------------|--|
| Date of Declaration | 28-02-2024 | |
| Primary Article Identifier | 4062172365307 | |
| Declaration No. in SCIP database | In work | |

Logistical Data

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|---|---------------------------------|--------------------------------------|-----------------------|--------------|
| 4062172365307 | Lightbar VX750-CB SR SM LEDDL124-CB SR SM | Folding carton box 1 | 905 mm x 110 mm x 123 mm | 12.24 dm ³ | 2328.00 g |
| 4062172365314 | Lightbar VX750-CB SR SM LEDDL124-CB SR SM | Shipping carton box 4 | 936 mm x 241 mm x 274 mm | 61.81 dm³ | 10243.00 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Safety advice

For detailed application information, please refer to the product data sheet and the user instruction

Legal advice

- 1) OSRAM LEDriving Driving Lights are approved according to ECE regulations and may therefore be installed and operated on public roads. Please note: Special installation regulations apply. In addition to ECE approval of the product, individual special requirements and legislation of the countries must be observed.
- 2) For precise conditions refer to: www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

