Product family datasheet

Lightbar VX1250-CB DR SM



Single mount certified For individual installation



Up to 410 m long beam Improved far and near field illumination



Combo beam Designed for both: far-field and near-field illumination



OSRAM

IP & IK protection classes Tested and validated in a DINcertified environmental simulation laboratory regarding extreme external influences such as water, dust, shocks, impacts, heat, cold, permanent vibrations and many more



Powerful LED driving lights for off-road and on-road use

Considerable foresight on dark country roads, forest paths, off the beaten tracks, off-road and on-road- this can be achieved with the OSRAM LEDriving Lightbar VX1250-CB DR SM. With its 108 powerful, high-performance LEDs, the driving light has a range of up to 410 meters and thus offers the driver impressive foresight on-road and off-road. Even in dim light and reduced visibility due to external environmental influences, the driving light with up to 6000 Kelvin can provide conditions similar to daylight. The power package with up to 13700 lumens scores with highest optical efficiency and homogeneous light distribution. The driving light is characterised by its robust double-row design, providing users with impressive illumination. In addition, the lightbar comes with standard brackets for various mounting options: hanging, standing and side. Versatile applicable, it defies numerous environmental influences and, thanks to high-quality materials such as the aluminum housing and the stable polycarbonate lens, it is particularly light and at the same time robust and resistant. The driving light has been tested and validated with the IP-Protection Classes IP6K8 & IP6K9K in our DIN certified environmental simulation laboratory for extreme external influences regarding water, dust, impacts, heat, cold and permanent vibration. Whether on-road or off-road, the LEDriving Lightbar VX1250-CB DR SM is an effective and efficient addition to your vehicle and can be attached to cars, trucks, agricultural machinery, commercial vehicles, construction vehicles, caravans, off-road vehicles and quads1). OSRAM provides a 2-year guarantee2).1) OSRAM LEDriving Driving Lights are approved according to ECE regulations and may therefore be installed and operated on public roads. Please note: Special installation regulations apply. In addition to ECE approval of the product, individual special requirements and legislation of the countries must be observed. 2) For precise conditions refer to: www.osram.com/am-guarantee

Product family datasheet

Technical data

	Product infor	Product information			Electrical data		Lifespan
Product description	Order reference	Application (Category and Product specific)		Nominal wattage	Test voltage	Luminous flux	Lifespan Tc
Lightbar VX1250-CB DR SM LEDDL127-CB DR SM	LEDDL127- CB DR SM Capabilities	applicatio single mo	l high beam n - central	162.00 W	13.2 V	13700 lm	> 5000 h
Product description	Technology	Approval marks – approval		Standards	s Type of protectio		
Lightbar VX1250-CB DR SM LEDDL127-CB DR SM	LED ¹⁾	Logistical data Environmer		ECE R10, R149 IP6K8/IP6K 9K			
	Logistical dat			Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)			
Product description	Commodity co	Commodity code		Date of Declaration			Declaration No. in SCIP database
Lightbar VX1250-CB DR SM LEDDL127-CB DR SM	85122000900	85122000900		40621723654		468	In work

 $^{1)}$ Light-emitting diode application

Product family datasheet

Download Data

	File
Z	User instruction LEDriving Lightbar VX1250-CB DR SM LEDDL127 CB DR SM

Safety advice

For detailed application information, please refer to the product data sheet and the user instruction

Legal advice

1) OSRAM LEDriving Driving Lights are approved according to ECE regulations and may therefore be installed and operated on public roads. Please note: Special installation regulations apply. In addition to ECE approval of the product, individual special requirements and legislation of the countries must be observed.

2) For precise conditions refer to: www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.