

LEDDriving SLT W5W

LEDDriving interior lamps for trucks



LED replacement lamp with a color temperature of up to 6,000 K

Modern and intense uniform illumination



Replaces all conventional W5W 24 V lamp bases

Easy upgrade to LED technology with plug & play solution



Reliable OSRAM quality stands for less lamp replacements

4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for W5W

LEDDriving SLT W5W replacement lamps offer a modern and intense light with a cool white color temperature up to 6,000 Kelvin. These replacement lamps are suitable for all conventional W5W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDDriving SLT lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product datasheet

Technical data

Product information

Product type (off-road vs. on-road)	Off-road \triangleq W5W
Application (Category and Product specific)	Mainly used for signal/ indicator/ interior applications

General Product Information

Global order reference	2845DWP
------------------------	---------


Electrical Data

Power input	0.7 W
Test voltage	28.0 V
Power input tolerance	± 25 %
Nominal wattage	1 W
Nominal voltage	24 V

Photometric Data

Color temperature	6000 K
Nominal luminous flux	65 lm
Luminous flux tolerance	± 25 %
Light color LED	Cool white

Physical Attributes & Dimensions



Product weight	1.70 g
Length	25.4 mm
Lamp base	W2.1x9.5d
Diameter	10.1 mm

Lifetime Data

Product datasheet

Lifespan Tc	3000 hr
Guarantee	4 years
Lifespan B3	1500 hr

Capabilities

Technology	LED
------------	-----

Environmental & Regulatory Information




Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Primary article identifier	4062172401814 4062172369626 4062172369657
Candidate list substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe use instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration no. in SCIP database	ce57cdf7-4612-4bc6-936c-acced2979e56 0aec2c32-bfb2-4cfc-8951-8fb05a649714 2fc75916-b507-420f-9a91-f93bb4a83a35

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172401814	LEDiving PREMIUM SL \triangleq W5W	BLI ECO 2	95 mm x 17 mm x 135 mm	0.22 dm ³	14.00 g
4062172401821	LEDiving PREMIUM SL \triangleq W5W	Shipping carton box 20	142 mm x 104 mm x 104 mm	1.54 dm ³	177.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

File
 User instruction GPRS_Safety symbols instructions
 Brochures LEDiving Retrofits - Exchange overview (EN)
 Brochures Sales Folder LEDiving replacement lamps (EN)

Safety advice

Product datasheet

Application advice:For more detailed application information and graphics please see product datasheet and user manual.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.



OSRAM