

LEDDriving SPK H7

LED high and low beam lamp as an easy replacement of conventional lamps




Up to +120 % more brightness

More light allows to see farther and therefore react sooner. Obstacles and hazards can be recognized sooner. In comparison with minimum ECE R112 requirements.



Cool White color temperature of 6,000 K

Better visibility thanks to daylight effect



1-year OSRAM guarantee

For precise conditions refer to www.osram.com/am-guarantee



High-performing LED retrofit lamp providing improved visibility

With a high power consumption of up to 54 W¹⁾, color temperature of 6,000 K and a very compact design the OSRAM LEDDriving SPK retrofits provide an easy solution to upgrade car headlights with cool white LED light – providing a stylish look as well as superior brightness of up to +120 %²⁾.

These LED high and low beam lamps as well as fog lamps³⁾ with high compatibility and easy installation replace conventional halogen lamps for a wide range of car models. LEDDriving SPK lamps are 12 V compatible. The pair of lamps comes with a 1-year⁴⁾ OSRAM guarantee and with a long service life.

- 1) Initial value of power consumption of a set with 2 lamps
- 2) In comparison to the minimum ECE R112 requirements
- 3) Please check the application compatibility
- 4) For precise guarantee conditions please refer to www.osram.com/am-guarantee

IMPORTANT: Sales allowed only in some specific countries in the regions CIS, Middle East and Africa: UAE, KSA, Kuwait , Qatar , Oman , Jordan , Lebanon, Iraq, Egypt , Morocco , Algeria , Tunisia, South Africa, Kazakhstan, Kyrgyzstan, Armenia.

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data



Product description	Electrical Data			Photometric Data	
	Nominal voltage	Nominal wattage	Test voltage	Nominal luminous flux	Luminous flux tolerance
LEDDriving SPK \triangleq H7	12 V	27 W	13.2 V	2000 lm	± 20 %

Product description	Physical Attributes & Dimensions	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)		
	Diameter	Primary article identifier	Candidate list substance 1	CAS No. of substance 1
LEDDriving SPK \triangleq H7	13.2 mm	4062172296892	Lead	7439-92-1

Product description	Safe use instruction	Declaration no. in SCIP database
LEDDriving SPK \triangleq H7	The identification of the Candidate List substance is sufficient to allow safe use of the article.	f69b3ce6-3e25-46dc-9d35-ecfa46898d26

Product family datasheet

Download Data

File	
	User instruction LEDriving HL SPK LED high and low beam 12V
	User instruction GPRS_Safety symbols instructions

Safety advice

Application advice:For more detailed application information and graphics please see product datasheet and user manual.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.