

XENARC NIGHT BREAKER 220



亮度最多可提高 220
照射距离更远，驾驶人员可以反应更迅速，与最低法律标准相比



长达250 m的远光
具有更高能见度



最高可達20%更白皙的光線
时尚外观，与最低法律标准相比



欧司朗功率最强的氙气灯

XENARC NIGHT BREAKER 220 is the brightest OSRAM xenon light. This powerful lamp with efficient xenon technology ensures a better visibility on the road: up to 220% more brightness compared to the minimum legal standard. More light allows to see further and therefore react sooner. Added to this is the up to 250 meter long beam and up to 20% whiter light for more modern look (compared to the minimum legal standard). Discover the pure performance of XENARC NIGHT BREAKER 220 - the most powerful xenon light from OSRAM, available in D1S, D2S, D3S and D4S. Please note: XENARC lamp change is recommended to be carried out by a professional and in pairs.

产品系列数据表

技术参数

产品描述	电参数				光度数据
	功率输入	标称电压	标称功率	测试电压	光通量
XENARC NIGHT BREAKER 220 D1S	35 W	85 V	35 W	13.5 V	3200 lm
XENARC NIGHT BREAKER 220 D2S	35 W	85 V	35 W	13.5 V	3200 lm
XENARC NIGHT BREAKER 220 D3S	35 W	42 V	35 W	13.5 V	3200 lm
XENARC NIGHT BREAKER 220 D4S	35 W	42 V	35 W	13.5 V	3200 lm

产品描述	光通量容许偏差	Physical Attributes & Dimensions	寿命		认证与标准	Environmental & Regulatory Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)
		直径	Lifespan B3	使用寿命 Tc	ECE 分类	Primary Article Identifier
XENARC NIGHT BREAKER 220 D1S	±15 %	9 mm	1500 hr	3000 hr	D1S ¹⁾	4062172398619 4062172397735
XENARC NIGHT BREAKER 220 D2S	±15 %	9 mm	1500 hr	3000 hr	D2S ¹⁾	4062172398640 4062172397766
XENARC NIGHT BREAKER 220 D3S	±15 %	9 mm	2000 hr	3000 hr	D3S ¹⁾	4062172398671 4062172397797
XENARC NIGHT BREAKER 220 D4S	±15 %	9 mm	2000 hr	3000 hr	D4S ¹⁾	4062172398701 4062172397827

产品描述	Candidate List Substance 1	CAS No. of substance 1	Safe Use Instruction	Declaration No. in SCIP database
XENARC NIGHT BREAKER 220 D1S	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	0682beb0-fcb6-4643-b1bf-f0df283c2352 5a5302eb-4799-4cbd-a466-1a125eac6e0a
XENARC NIGHT BREAKER 220 D2S				In work
XENARC NIGHT BREAKER 220 D3S	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	2322ca85-73dd-494d-97a0-7d1ae5c23717 3dea30b6-ada1-419d-b9db-7582b1c7f8bf
XENARC NIGHT BREAKER 220 D4S				In work

¹⁾ 仅可使用经过认证的电子控制装置运行

产品系列数据表

下载数据

文件	
	User instruction GPRS_Safety symbols instructions
	Addon Technical Information Product Certificates HID
	ref_pim_amsproduct360degreeimages XENARC ORIGINAL D1S 66140
	ref_pim_amsproduct360degreeimages XENARC NIGHT BREAKER D2S 66240XNB
	ref_pim_amsproduct360degreeimages XENARC NIGHT BREAKER D3S 66340XNB
	ref_pim_amsproduct360degreeimages XENARC NIGHT BREAKER D4S 66440XNB

安全建议

XENARC lamps should be replaced by a qualified mechanicThis product must only be operated with approved electronic control gear

法律建议

Light output compared to the minimum ECE R112/R37 requirementsThis product must only be operated with approved electronic control gearXENARC lamps should be replaced by a qualified mechanicReduced UV emission | For projection headlights | ECE approval and DOT label± 450 lm

应用建议

更多详细应用信息和图形,请参阅产品数据表。

免责声明

更改恕不另行通知。遗漏错误不承担任何责任。总是确保使用最新的信息。