Product datasheet

Wire Harness AX 1LS

Connection of one light source
Wire harness suitable for the installation of one light source with one lighting function of the OSRAM LEDriving driving and working lights for 12 V vehicles

On/Off switch integrated
For installation in the vehicles cabin to switch the OSRAM LEDriving working lights on or off as required

Easy Installation
For easy installation of OSRAM LEDriving driving and working lights

Bringing light to life with OSRAM LEDriving driving and working lights

To support the installation of the OSRAM LEDriving driving & working lights, OSRAM has developed a special series with suitable accessories for them. With the OSRAM Wire Harness AX 1LS, the OSRAM LEDriving driving & working lights, can now be installed quickly and easily on the appropriate vehicle.

The OSRAM Wire Harness AX 1LS is a wire harness that is suitable for the installation of one light source with one lighting function. It also has an integrated on/off switch that can be installed in the vehicles cabin to switch the OSRAM LEDriving working lights on or off as required. The switch is only to be used for the OSRAM LEDriving working lights. The OSRAM Wire Harness AX 1LS is suitable for 12 V vehicles. OSRAM also offers a 2-year guarantee[1)].

© 2026, OSRAM GmbH. All rights reserved.

Product datasheet

Technical data

General Product Information

Global order reference	LEDDL ACC 101

Electrical Data

Nominal voltage	12 V

Physical Attributes & Dimensions





Product weight	275.00 g

Lifetime Data

Guarantee	2 years

Logistical data

Commodity code	85444290900

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)	
Primary article identifier	4062172147682
Candidate list substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe use instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration no. in SCIP database	572d3ab9-d00d-4909-ab5b-a808fb524404

Logistical Data

© 2026, OSRAM GmbH. All rights reserved.

Product datasheet

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172147682	Wire Harness AX 1LS	Folding carton box 1	175 mm x 81 mm x 177 mm	2.52 dm^3	325.00 g
4062172147699	Wire Harness AX 1LS	Shipping carton box 8	362 mm x 335 mm x 190 mm	23.04 dm^3	3045.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

	File
	User instruction GPRS_Safety symbols instructions
	Movie application LEDriving D and W Image Video Bringing light to life (EN)
	Movie application LEDriving Driving and Working Lights Reference Video (EN)
	Movie application OSRAM LEDdriving and working lights Imagefilm (EN)
	Movie application OSRAM Quality Testing LEDriving working and driving lights (EN)

Legal advice
Legal advice:

1) Precise terms and conditions at: www.osram.com/am-guaranteeApplication advice:

For more detailed application information and graphics please see product datasheet and user instruction.

Application advice
For more detailed application information and graphics please see product datasheet.

Disclaimer
Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2026, OSRAM GmbH. All rights reserved.